

## SUGGESTED INSTALLER CHECKLIST

February, 2006 Revised: June 2012

Form № 0531

## **Tools - Suggested**

- 1. Auto leveling laser with receiver 2nd receiver helpful for larger slabs.
- Saws handsaw, keyhole / pruning saw, small chainsaw, battery reciprocating saw with long blade, circular saw, and for heated slabs only, chop saw and spare blades (metal for steel pipe and 60+ tooth for plastic pipe).
- 3. Utility knife, extendable blade recommended such as H-1 Olfa.
- 4. Battery drills with magnetic 1/4" hex drivers (heated slab only)
- 5. Tape measures.
- 6. Chalk line with red chalk.
- 7. Drywall T-square.
- 8. Framing square.
- 9. Lumber crayons, magic markers, pencils or line marking spray paint (*inverted cans*). (heated slab only)
- 10. Tin snips.
- 11. Hammers claw and small sledge.
- 12. Bolt cutter.
- 13. Shovel and wheelbarrow.
- 14. Landscaping rake (36" wide) and comb rake.
- 15. Rebar tie spinners or hook for drill.
- 16. Generator if power not available (including gas, oil).
- 17. Extension cords.
- 18. Flood lights if required.
- 19. Small (18") plate packer or small vibrating roller.
- 20. Digital camera.
- 21. Hearing, eye, hand, foot and head protection.
- 22. Architectural drawings for building to verify dimensions, possible interferences (*floor drains, plumbing etc.*), and for heated slabs, conduit locations and verify heater box locations are in appropriate locations.
- 23. Scale ruler 1/4" = 1' or 1/2" = 1' depending on plan scale
- 24. Provisions for waste disposal.
- 25. Low expansion foam gun (for low expansion foam cannisters supplied with heated slabs only).

## **Materials - Suggested**

- 1. Batter boards 2x2 stakes, 1x4 strapping, 1-1/2" wood screws and mason line.
- 2. 5"-6" spiral nails.
- 3. Wire mesh and rebar as per drawing.
- 4. Dowels (ICF walls) or anchor bolts (wood frame walls).
- 5. Angle for garage doors (optional).
- 6. Rigid and/or flexible electrical conduit, complete with fittings, locknuts and PVC cement (refer to Rough-In PDS for sizes for electrical and water lines). (heated slabs only)
- 7. 1/2" oxygen barrier PEX for water lines (*cut ends at 45*° *for ease of installation in sleeves*). (heated slabs only)
- 8. Wire pulling lubricant for long water line runs. (heated slabs only)
- Patio stone or cinder block or large stone to weigh down furnace box. (heated slabs only)